



# SEISMIC SEALTITE


## PRODUCT DESCRIPTION

- Seismic Sealtite is a premium quality joint sealant composed of an open micro-cell polyurethane foam impregnated with a hydrophobic, polymer sealing compound
- Seismic Sealtite is supplied precompressed
- Seismic Sealtite is designed to function as a vertical primary seal in construction joints; expansion joints; and control joints



## COLORS

Tremco Spectrem® colors (pictured below) and other colors available by request



## LIMITATIONS AND INSTALLATION CONSIDERATIONS

- Joints must be sized by measuring every 5 – 7 feet to ensure gap opening is uniform and depth is sufficient for the supplied material
- Will not adhere to surfaces contaminated by oil, grease, or dust
- Store material in a dry, enclosed area, off the ground, and out of direct sunlight. Do not install when raining or snowing

## NOT INTENDED FOR

- Joints submerged in water
- Joints in contact with harsh chemicals
- Horizontal joints
- Cross joints in copings and projecting stonework

## WARRANTY

Schul Products are warranted to be free of defects in materials, but no warranty is made as to appearance or color. No other warranty, expressed or implied, is made with respect to Schul Products, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE. The sole and exclusive remedy under this warranty shall be to replace or refund the purchase price of the quantity of Schul Products proven to be defective, and there is no liability whatsoever for other loss or damage.



INTERNATIONAL QUALITY REGISTRARS CORP.  
QUALITY SYSTEM REGISTRATION; ISO 9001 CERTIFIED



MADE IN THE USA  
FROM DOMESTIC AND IMPORTED COMPONENTS

SCHUL INTERNATIONAL COMPANY  
TELEPHONE: (800) 848-1120 • FAX: (800) 998-9105 • WEB ADDRESS: [www.schul.com](http://www.schul.com)  
34 EXECUTIVE DRIVE, HUDSON, NH 03051